


# H.264 IP 2 MEGA PIXEL CMOS CAMERA

## YUC-H696

### Feature

- 2 Mega pixel (1600 x 1200) progressive scan
- H.264/MPEG-4/JPEG triple streams simultaneously
- Up to 32G SD card recording for alarm trigger & network outage
- IR cut removal (ICR) for option
- 2-way audio
- Mobile view support
- WiFi / PoE support



Server	Network Compression	Triple streams:H.264/MPEG-4/JPEG
	Pixel (H x V)	1600x1200, 1280x1024, 1280x960, 1280x720, 800x592,640x480, 320x240, 176x144
	Traffic Control	32/48/64/96/128/196/256/320/384/448/512/576/640/704/768Kbps 1/1.5/2/2.5/3/3.5/4/6/8Mbps
	Max. Frame Rate	Max. 30FPS (1280x720, 800x592, 640x480, 320x240, 176x144), 25FPS (1280x960), 22FPS (1280x1024), 15FPS (1600x1200)
	Safety	User-ID and password
	Protocol	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, PPPoE, DNS, DDNS, NTP, UPnP, UPnP forwarding, RTSP
	Number of User	Max. 10 connections for singal video
	Storage Capacity	SD card
	Alerting	SMTP, FTP, HTTP, SD card
	Pre / Post Alarm	Pre (0,1,2,3,4,5), post(0,1,2,3,4,5,10) seconds
	Release for alarm	Motion detection, I/O or schedule
Network Camera	Image Pick-up Device	1/3" Progressive Scan CMOS sensor, approximately 2 mega pixel
	BLC	Auto (ON/OFF)
	Electronic Shutter	1/50 (1/60) ~ 1/100,000 second
	Video Output	BNC, 1Vp-p, 75 Ohms
	Min Illum.	0.1 - 100.000 Lux (in night color mode 0.01-100.000 Lux)
Audio	Lens	CS mount (DC driver supported)
	Optical	IR cut filter as option
	Audio Communication	2-way-halfduplex
	Audio Compression	ADPCM 32Kbps
	Frequency	300 Hz - 3.4KHz
Terminal	Audio In	Microphone built in
	Audio Out	RCA, line out for external speaker
	Network Interface	Ethernet(10Base-T/100Base-Tx), WiFi for option
	Video Interface	BNC, video composi (NTSC/PAL)
General	External Port	Alarm-in x1 / relay-out x1, RS485 2 wires
	SD Card	SD memory card with the 32GB, 16GB, 8GB, 4GB~64MB
	Operation Voltage	PoE: 48V, IEEE 802.3af for option (max. 7W) LAN: 12V DC (max. 6W), WiFi: 12V DC (max. 7W)
	Dimen./Weight	58(H)x65(W)x130(D)mm / @400g / 12pcs per carton
	Operation Temp.	-10°C ~ +45°C, relative moisture 20%-90%

### Order Reference

YUC-H696P: PoE \ YUC-H696RP: ICR/PoE \ YUC-H696W: WiFi \ YUC-H696RW: ICR/WiFi